

Atecpool Ocea Laminated Filter


Ocea Laminated Filter Specifications

Atecpool innovative design and advanced technology offers superior filtration performance and crystal clear water. Body in laminated Fiberglass and reinforced polyester making the filter totally anti-corrosive.

- Maximum working temperature : 40°C
- Fiberglass reinforced polyester base
- Injected interior parts in ABS and PVC
- Collector system using laterals 0.3mm slot


- Closed top lid in two options
 - Transparent Glass Lid with nuts and gaskets
 - Injected ABS with nuts and gaskets
- Equipped with 2" sand/water drain
- All gaskets in silicon
- Maximum working pressure: 2.5 kg/cm².
- Supplied with MPV

Ocea Top Mounted Sand Filters



Code	Diameter	Max Flow	Valve Connections	Sand
	Ø mm	m ³ /h	mm	kg
065450	450	8	50	80
065500	500	10	50	90
065650	650	15	50	140
065760	760	22	63	305
065800	800	24	63	325
065950	950	30	63	530

Ocea Side Mounted Sand Filters



Code	Diameter	Max Flow	Valve Connections	Sand
	Ø mm	m ³ /h	mm	kg
069450	450	8	50	80
069500	500	10	50	90
069650	650	15	50	140
069760	760	22	63	305
069800	800	24	63	325
069950	950	32	63	530

Maximum filtration velocity: 50m³/h/m² - Maximum working pressure: 2.5 kg/cm² - Testing Pressure: 4kg/cm².

Code	Diameter	Valve Connection	Filtration Area	Dimensions (mm)			
				A	B	D	
TOP MOUNTED				mm			
	Ø mm	mm	m ²				
065450	450	50	0.14	650	830	450	
065500	500	50	0.20	750	930	500	
065650	650	50	0.30	850	1030	650	
065760	760	63	0.42	1000	1180	760	
065800	800	63	0.46	1030	1210	800	
065950	950	63	0.60	1030	1210	950	
SIDE MOUNTED				mm	A	B	D
							C
069450	450	50	0.16	290	410	450	700
069500	500	50	0.20	300	420	500	800
069650	650	50	0.30	320	440	650	900
069760	760	63	0.44	360	560	760	1030
069800	800	63	0.48	380	580	800	1080
069950	950	63	0.64	380	580	950	1080

These codes include the filter valve. Velocity=50m³/h/m²

Recommended to be used with Activated Filtration Media

