

Salt Water Electrolysis

AT-Series Salt Chlorinator Combined Pack

Atecpool Salt Chlorinator combined unit - 3 Packs

1



Code: ATECPACK001

AT-Series Wireless Salt Water Chlorinator + pH Wireless Pump

pH Wireless Chlorinator

- Wireless Chlorinator with pH control connect to wireless pH Dosing pump via radio frequency.
- pH electrode connected to wireless chlorinator, shows pH display.
- Easy user interface with backlit LCD.

pH Wireless Pump

- Longe range wireless dosing pump upto 50 mts.
- Peristaltic wireless pump will start and stop functioning depending on the set points assigned from Salt Chlorinator menu.
- Allows installation away from the chlorinator or outside the filtration room to avoid damages by the acid.

- Self cleaning cell.
- Wall mounting with independent stainless steel bracket.
- Detachable plug for a faster service.

- Easy calibration and configuration through the chlorinator LCD.
- Proportional dosage control.
- Flow: 1.5 l/h. Pressure 1.5 bar.
- Manual priming button.

2



Code: ATECPACK002

AT-Series Salt Water Chlorinator + pH Basic Controller

pH Basic Controller

- Autonomous pH regulator.
- Integrated peristaltic transparent acid pump 1.5 l/h – 1.5 bar.

- Interchangeable peristaltic head without screws.
- Agile menu system and easy calibration.
- pH range: 0 - 14.

Elements included

- Control panel with peristaltic pump.
- pH probe.
- Acid aspiration tube.
- Acid injection tube.
- Suction filter with weight.

- Injection fitting.
- Probe holder.
- Collars (2) for 50 mm tube.
- pH4 and pH7 buffer solutions.

Technical Features

- Power supply 230 VAC 50-60 Hz.
- Power consumption 20 W.

- Packaging weight 1 Kg.
- Packaging dimensions 22x13x10 cm.

3



Code: ATECPACK003

AT-Series Salt Water Chlorinator + pH Redox Controller

pH Redox Controller

- Autonomous pH and ORP regulator.
- pH range: 0 - 14.
- ORP range: 0 – 1000 mV
- ORP measurement of 0 to 1,000 mV.

- Integrated peristaltic transparent acid pump 1.5 l/h – 1.5 bar.
- Interchangeable peristaltic head without screws.
- Agile menu system and easy calibration.

Elements included

- | | | |
|--|-------------------------------|---------------------------------|
| • Control panel with peristaltic pump. | • Acid suction tube. | • Probe holder (2). |
| • pH probe. | • Acid injection tube. | • Collars (3) for 50 mm tube. |
| • ORP probe. | • Suction filter with weight. | • pH4 and pH7 buffer solutions. |
| | • Injection fitting. | • Redox buffer solution. |

Technical Features

- Power supply 230 VAC 50-60 Hz.
- Power consumption 20 W.

- Packaging weight 1 Kg.
- Packaging dimensions 22x13x10 cm.