Pool Fittings Main Drains

Circular Main Drain

Circular main drain in UV treated white ABS Ø210 mm, 2" threaded side outlets, grill fitted with screws. Max flow rate 12 m³/hr, designed for surface suction velocity not exceeding 0.5 m/s. For liner model supplied with self-adhesive gaskets, flange and screws.





Code	Description	Std packing	Weight
			(kg)
01592832	Circular Main Drain Concrete	1	0.6
01592832-1	Circular Main Drain Liner	1	0.6



Square Main Drain

Square Main Drain in UV treated white ABS 210 x 210 mm, 2" threaded side outlets. Maximum Flow rate 13 m³/hr. For liner model supplied with selfadhesive gaskets, flange and screws. Grille 175 x 175 mm.

Code	Description	Std packing	Weight
			(kg)
03100258	Square Main Drain Concrete	1	1
03100258-1	Square Main Drain Liner	1	1.2

Anti-Vortex Main Drain

Circular main drain in UV treated white ABS Ø210 mm, 2" threaded side outlets, anti-vortex grill fitted with screws. Max flow rate 13 m³/hr, designed for surface suction velocity not exceeding 0.5 m/s. For liner model supplied with self-adhesive gaskets, flange and screws.



Code	Description	Std packing	Weight
			(kg)
03100257	Circular Main Drain Antivortex Concrete	1	0.6
03100257-1	Circular Main Drain Antivortex Liner	1	0.6



Square Main Drain AISI 316

Made of stainless steel AISI 316, square main drain 150 x 150 mm, 100mm height, 2" female threaded side connection. Grille 146 x 146 mm fixing using screws. Flow rate: 13.5 m²/hr.

Code	Description	Std packing	Weight	
			(kg)	
031002595	Square Main Drain AISI 316	11	3	

Drain Grilles



Circular Drain Grille ABS

Circular drain grille and ring support in white ABS. Ø200mm, supplied with fixing screws. Max flow rate 13 m³/hr.

Code	Description	Size	Std packing	Weight
		(mm)		(kg)
10534100	Circular Drain Grille ABS	Ø200	1	0.3



Circular Drain with S.S. Grille Support ring in UV treated white ABS, circular grille Ø200mm made of stainless steel AISI 316. Supplied with grille fixing screws. Recommended flow rate 13 m³/hr.

Code	Description	Size	Std packing	Weight
		(mm)		(kg)
10532116	Circular Drain with SS Grille	Ø200	1	1.2



Anti-Vortex Drain Grille ABS Circular antivortex drain grille and in white ABS. Ø170mm. Maximum flow

Code	Description	Size	Std packing	Weight
		(mm)		(kg)
10532100	Antivortex Drain Grille ABS	Ø170	1	0.3

rate 12 m³/hr.



Anti-Vortex Drain Grille AISI 316 Support ring and circular grille Ø220mm made of stainless steel AISI 316. Supplied with grille Ø185mm and fixing screws. Recommended flow rate 14 m³/hr.

Code	Description	Size	Std packing	Weight
		(mm)		(kg)
10532115	Anti-Vortex Drain Grille AISI 316	Ø220	1	1.5